

**Professional Wireless Security,  
Now with Live Video Verification!**



**Agility™3, the two-way wireless security and safety system now offers more! This popular cloud-based system is compatible with VUpoint, RISCO Group's revolutionary live video verification solution that utilizes IP Cameras to provide real-time video streaming in response to triggers, or on demand.**

**Agility™3 with VUpoint offers an unrivalled and cutting edge security solution for homes and small businesses that is flexible, reliable and easy to install.**

- Professional security solution with live video verification will increase your sales potential
- IP Cameras support easy plug & play installation; no specialized training required
- One intuitive smartphone app can be used for both visual verification by event using snapshots, and live video verification in response to alarm triggers or on demand, in addition to control on the go
- Advanced security and monitoring capabilities available for both monitoring stations and end-users



### eyeWave™ Wireless PIR/PET Camera

- Wireless PIR/PET detector with integrated camera
- PIR coverage 12m wide angle
- VGA/QVGA resolution with 85° field of view
- Discreet IR flash provides imaging in complete darkness, up to 10m range
- Battery save mode while system is disarmed
- Can be triggered from different system events



### Security

- Complete range of wireless indoor, outdoor and perimeter detectors
- Indoor and outdoor wireless sounders



### Outdoor & Perimeter

#### Wireless WatchOUT™

- Reliable outdoor detection with 2 PIR channels, and IP65 rating
- 1-Way and 2-Way versions available

#### Wireless Beams

- Reliable perimeter detection
- Direct sunlight immunity
- 1-Way and 2-Way versions available



### Safety

- Smoke, Gas, CO and Flood detectors



### Elderly Care

- Stylish and water-resistant Wristband Panic Transmitter
- Alerts if an elderly parent is immobile in the home over a defined period



### Home Automation

- 2-Way wireless Input/Output Expander
- 4 wired inputs and 4 outputs



### 2-Way Wireless LCD Keypad

- Integrated proximity reader for arm/disarm
- Adaptive menu displays only the relevant options according to the installation and set up



### 2-Way Wireless Slim LED Keypad

- Full system user operation
- Door chime feature
- Outdoor version available
- Available with Proximity Reader



### 2-Way Remote Control

- Multi color LEDs indication for system status
- PIN code for higher security



### VUpoint - Live Video Verification

- Agility™3 with VUpoint is powered by the RISCO cloud and offers live video streaming in response to alarm triggers or on demand, providing unsurpassed security and control
- Immediate and reliable video verification of intruder alarms, or live video on demand
- Analyze pre and post-alarm video clips of intruder events
- Control and view with smartphone app, web browser or tablet keypad
- Unlimited number of IP Cameras can be supported



### Main Panel

- Dual Core Wireless provides two simultaneous 2-Way wireless channels with separate antennas - one for alarm, control and diagnostic signals, a second for video image transmission
- SIA-IP support provides a protocol for enhanced communication with monitoring stations
- Digital Voice Module for enhanced voice quality
- Multi-lingual support for voice and keypad display



**Selection of IP Cameras Available**

With VUpoint there is no limit to the number of IP cameras that can be installed and configured to the intrusion system, thereby providing increased revenue potential for installers. IP Cameras are available for both indoor and outdoor environments and provide a cost-effective security solution for homes and businesses.



RISCO Cloud Server

GSM/GPRS

IP/Internet

PSTN/Dial Up




**Live Video Verification**

Agility™3 with VUpoint offers live video streaming in response to alarm triggers or on demand, providing unsurpassed security and control.

**Smartphone App and RISCO Cloud**

Powered by the RISCO Cloud, home and business owners can use the iRISCO smartphone app for both visual verification by event using snapshots, and live video verification in response to alarm triggers or on demand. The app can also be used for arming and disarming per partition, and viewing a history log of events.



Monitoring Station



**Web Application**

RISCO Group's interactive web application enables homeowners to monitor, control and configure their Agility™ system from any location. In addition to all the capabilities of the smartphone app, with the web application users can also configure RISCO's PIR Camera settings such as the number of images taken, image resolution, and more. The application is powered by the RISCO Cloud server.

**Remote Upgrade & Configuration Software**

RISCO Group's Configuration Software saves installers time and money by enabling simple installation, remote configuration, automatic system diagnostics and remote upgrade of the Agility™ panel.



Agility™3 offers a complete range of wireless safety, security and home automation accessories, both 1-way and 2-way, that can be seamlessly combined in the same installation.



### Technical Specifications

Wireless zones (1-Way or 2-Way)	32
Partitions	3
Wireless Sounders (2-Way)	3 (Indoor or outdoor)
Wired Zones	4 (with I/O Expander)
Wired Outputs	4 (with I/O Expander): 2x3A relay and 2x500mA
IP Camera (Internal/External)	Unlimited number supported through the Cloud server
Wireless PIR Cameras	8
Keypads (2-Way)	3 - LCD or Slim (Internal/External)
Remote Controls (1- Way or 2-Way)	8 (4 button or 8 button)
X-10	Supported with I/O Expander
User codes	32
Event log	250
Monitoring Station Accounts	3
Follow-me destinations	16
Communication	PSTN, IP, and GSM/GPRS in any combination
Reporting formats	Contact ID, SIA level 2 & 3 (text support), IP/GSM Receiver, SIA IP (with encryption)
Installer Programming Methods	Local using RS232 for Configuration Software Local using LCD 2-Way keypad Remote using configuration software (GPRS, IP, PSTN) direct or through the cloud
Firmware upgrade	Local or remote via GPRS or IP
Automated scheduling	8 (Arm/Disarm or output control)
End user features	<ul style="list-style-type: none"> <li>• <b>New</b> - Smartphone apps and web browser for video verification, arm/disarm, control and monitoring the system</li> <li>• Email: Event and images notification</li> <li>• SMS: Event notification and remote control</li> <li>• Audio: Voice event messaging, touch-tone control with full voice menu guide, two-way audio for listen-in and speak-in</li> <li>• Push notifications, Live video stream with recording capabilities</li> </ul>
Dimensions (H x W x D)	268.5 x 219.5 x 64 mm (10.57 x 8.64 x 2.52 inch)
Approvals	EN50131 Grade 2, Class II; EN50136; INCERT; SBSC

Specifications subject to change without prior notice.



For more information about RISCO Group's branches, distributors and full product line, please visit [riscogroup.com](http://riscogroup.com)

